




THE BENCHMARK OF BUSINESS PRINTING



imageCLASS MF416dw marks a new professional standard for business printing. From small, medium to large enterprises, it is highly efficient and geared to boost work productivity in the office. Beyond accelerated print speeds and higher yields, it is also economical, eco-friendly and simple to use. Featuring the newly-improved interface with colour touch-screen display, navigation is made easy and intuitive to use. Optimised for a smart connected office, you can seamlessly connect the device to the network wirelessly and print from your mobile terminals.

PERFORMANCE PRODUCTIVITY



SUPERB PRINT SPEED

Have your first printout ready in 6.3 seconds or less, with print and copy speeds of 33ppm for A4 documents.



HIGHER CAPACITY FOR GREATER POSSIBILITIES

imageCLASS MF416dw handles demanding print volumes with a 50-sheet multi-purpose tray. It also caters for an optional 500-sheet paper feeder for high print volumes of up to 800 sheets.

ADVANCED FUNCTIONALITY



PEACE OF MIND

Use Secure Print to print your confidential data and protect sensitive documents from being seen by an unauthorised person. With Department ID Management, your IT administrator can easily manage the device and evaluate print usage.



REMOTE SUPPORT

With the web-based Remote UI Interface, IT Administrators can now check the printer status and manage print operations in one single interface from the comfort of their own desks.

INTUITIVE CONVENIENCE







WIRELESS CONVENIENCE

Discover a suite of wireless possibilities in your everyday operations. Canon's PRINT Business app enables you to print a variety of file types wirelessly to the printer from both iOS and Android devices. With AirPrintTM, you can print documents directly from Apple® devices without the hassle of installing printer drivers, while Google Cloud PrintTM compatibility allows you to print to your web connected printer from virtually anywhere. Enjoy the added convenience of contactless printing with the NFC-enabled device, just tap to print.

*AirPrint is a trademark of Apple Inc



USER-FRIENDLY INTERFACE

Designed with 3.5" QVGA 7-line colour touch-screen LCD display panel for intuitive usage and navigation.





*Images for illustration purposes only

7-LINE COLOUR TOUCH-SCREEN LCD

Cartridge 319
GENUINE

MINIMAL MAINTENANCE

Canon All-in-One toner cartridge 319 requires little upkeep. You also have the luxury of high-yield replacement toner cartridge (up to 6,400 pages) to further lower operating costs and reduce the frequency of replacement.



SEAMLESS NETWORK

Connect to a wireless LAN or Ethernet network for easy printer sharing. For individual usage, you can also connect to any PC via the USB2.0 High Speed port.

ECO-EFFICIENCY



DUPLEX SAVINGS

Save on paper usage with two-sided prints. The duplex printing mode helps you save on paper consumption by printing on both sides, effectively cutting paper usage by half.



GREEN CAPABILITIES

Reduce power consumption when the printer is not in use with the Sleep Mode. Cut down on paper wastage with the PC Fax feature that enables you to send faxes directly from your PC.

VERSATILE CONNECTIVITY

FOR PRINT PERFORMANCE

imageCLASS MF416dw comes with Adobe® PostScript® 3^{TM} technology to deliver industry-standard precision in graphic and CAD printing. Equipped with high-speed gigabit Ethernet interface, it allows high-volume data transmissions to optimise your workflow.





PRINT				
Printing Method		Monochrome Laser Beam Printing		
Print Speed (A4)	Up to 33ppm		
Print Resolution		600 x 600dpi		
Print Quality wit		1200 x 1200dpi (equivalent)		
Refinement Tecl	(From Power On)	2400 (equivalent) x 600dpi 16.0 sec or less		
First Printout Tim		6.3 sec or less		
Recovery Time	ie (IFOI) A4			
(From Sleep Mo	de)	5.0 sec or less		
Print Language		UFR II, PCL 6, Adobe® PostScript® 3™		
Auto Duplex Print		Standard		
Available Paper Size for Auto Duplex Print		A4, Legal*1, Letter, Foolscap, Indian Legal		
Print Margins		10mm - top, bottom, left, right (Envelope Size) 5mm - top, bottom, left, right (Other than Envelope Size)		
Direct Print from	USB	Supported File format: JPEG, TIFF, PDF		
Print Features		Poster, Booklet, Watermark, Page Composer, Toner Saver		
COPY				
Copy Speed (A4)	Simplex	Up to 33ppm		
Copy Resolution	n	Up to 600 x 600dpi		
First Copy Time		10.0 sec or less		
Maximum Num	ber of Copies	Up to 999 copies		
Reduce / Enlarg	gement	25 - 400% in 1% increments		
Copy Features		Frame Erase, Memory Sort, 2 on 1, 4 on 1, ID Card Copy		
SCAN				
Scan Type		Colour Contact Image Sensor		
Scan Resolution	1	Optical: Up to 600 x 600dpi, Driver Enhanced: Up to 9600 x 9600dpi		
Scan Speed		Approx. 3 sec per sheet (Monochrome) Approx. 7 sec per sheet (Colour)		
Colour Depth		24-bit		
Duplex Scan		Yes		
Pull Scan		Yes, USB and Network		
Push Scan (Sca with MF Scan U	tility	Yes, USB and Network		
Scan to USB (vi	a USB Host)	Yes		
Scan to Cloud		MF Scan Utility		
Scan Features		TWAIN, WIA (Scan Driver Compatibility)		
SEND				
Send Method		SMB, E-mail, FTP, iFAX Simple		
Colour Mode		Full Colour, Grayscale, Monochrome		
Scan Resolution		300 x 300dpi, 200 x 200dpi		
File Format		JPEG, TIFF, PDF, Compact PDF, PDF (OCR)		
FAX		Ha do 33 6Vhan		
Modem Speed Fax Resolution		Up to 33.6Kbps		
	ethod	Up to 406 x 391dpi		
Compression Method		MH, MR, MMR, JBIG		
Memory Capacity ² Favourite Dials		Up to 512 pages		
(in address book)		19 dials		
Coded Dials		Up to 281 dials		
Group dials / Destinations		Max. 199 dials / Max. 199 destinations		
Sequential Broadcast		Max. 310 destinations		
Receive Mode		Fax Only, Manual, Answering, Fax / Tel Auto Switch		
Memory Backup		Permanent fax memory backup. (Backup with flash memory)		
Fax Features		Fax Forwarding, Dual Access, Remote Reception, PC Fax (Transmission only), DRPD, ECM, Auto Redial, Fax Activity Reports, Fax Activity Results Reports, Fax Activity Management records		
Transmission Time		Approx. 3 sec		
Transmission fine		. 4-1		

*1 Legal size refers	to paper	size measurina	215.9 x 3	355.6mm	(8.5 x14inch).
2090, 020 101010	o pape				

² Based on ITU-T #1 Chart (standard mode)

PAPER HANDLING					
Duplex Auto Document Feeder (DADF) (Based on 80g/m²)		50 sheets			
Available Paper Size for ADF		A4, B5, A5, B6, Letter, Legal, Statement (Min. 128 x 139.7mm to Max. 215.9 x 355.6mm)			
Paper	Standard Cassette	250 sheets			
Input (Based on Plain Paper	Multi-Purpose Tray	50 sheets			
	Optional Paper Feeder	500 sheets			
60-89g/ m²)	Maximum Paper Capacity	800 sheets			
Paper Out	out	150 sheets (face down), 1 sheet (face up)			
Paper Sizes	Standard Cassette / Optional Paper Feeder	A4, B5, A5, Legal, Letter, Statement, Executive, Government Letter, Government Legal, Foolscap, Indian Legal Custom: Min. 105 x 148mm to Max. 215,9 x 355.6mm			
	Multi-Purpose Tray	A4, B5, A5, Legal, Lefter, Statement, Executive, Government Lefter, Government Legal, Foolscap, Indian Legal, Postcard, Index card Envelope; COM10, Monarch, C5, DL Custom: Min. 76.2 x 127mm to Max. 215.9 x 355.6mm			
Paper Type	es	Plain, Heavy, Recycled, Colour, Label, Postcard, Envelope			
Paper Weight	Standard Cassette / Optional Paper Feeder	60 - 128g/m ²			
	Multi-Purpose Tray	60 - 163g/m ²			
CONNECT	IVITY & SOFTWARE				
Standard	Wired	USB Device 2.0 High-Speed, 10/100/1000 Base-T Ethernet (Network)			
Interfaces	Wireless	Wi-Fi 802.11b/g/n (Infrastructure mode, WPS Easy Setup), Direct Connection			
Near Field (NFC)	Communication	Yes (Passive)			
Network Protocol		Print: LPD, RAW, WSD-Print (IPv4,IPv6): Scan: Email, SMB, WSD-Scan (IPv4, IPv6): TCP/IP Application Services: Bonjour(mDNS), HTTP, HTTPS, POP before SMTP (IPv4,IPv6), DHCP, ARP+PING, Auto I; WINS (IPv4), DHCPv6 (IPv6) Management: SNMPv1, SNMPv3 (IPv4,IPv6)			
Network	Wired	IP/Mac address filtering, HTTPS, SNMPv3, IEEE802.1x			
Security	Wireless	WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES)			
One-Push \ Configurat	ion	Wi-Fi Protected Setup (WPS)			
Departme	nt ID	Yes, up to 300 IDs			
Mobile Sol	utions	Canon PRINT Business, AirPrint™, Mopria® Print Service, Google Cloud Print™, Canon Print Service			
Address Bo	ook	LDAP			
Compatible Operating Systems ^{*3}		Windows® 10, Windows® 8.1, Windows® 8, Windows® 7, Windows® Vista, Windows® Server 2012 R2, Windows® Server 2012, Windows® Server 2008 R2, Windows® Server 2008 R2, Windows® Server 2003, Mac OS X 10.6 & up. Linux*4			
Software Included		Printer driver, Fax driver, Scanner driver, Network Scan Utility, MF Scan Utility, Presto! PageManager, Toner Status			
GENERAL	SPECIFICATIONS				
Device Me		1GB			
LCD Displo	ıy	3.5" QVGA Colour Touch-Screen			
	s (W x D x H)	Normal State: 390 x 473 x 431 mm With the installation of Optional Paper Feeder: 390 x 473 x 566.7 mm			
Weight		18.5kg (without cartridge) 19.2kg (with cartridge)			
	Maximum	1,160W or less			
Power Consump-	Average (During Operation)	Approx. 590W			
Consump- tion	Average (During Standby)	Approx. 9.4W			
	Average (During Sleep)	Approx. 1.4W (USB), Approx. 1.5W (wired LAN), Approx 2.1W (wireless LAN)			
Noise	During Operation	Sound Pressure Level (Bystander's position): 53.0dB, Sound Power Level: 70.6dB or less			
Levels*5	During Standby	Sound Pressure Level (Bystander's position): Inaudible*6, Sound Power Level: 53dB or less			
Operating Environment		Temperature: 10 - 30°C Humidity: 20% - 80% RH (no condensation)			
Power Req	uirements	AC 220 - 240V (+/-10%), 50/60Hz (+/-2Hz)			
Toner Cartridge ¹⁷		Cartridge 319: 2,100 pages, Cartridge 319 II: 6,400 pages			
Monthly Duty Cycle ¹⁸		Up to 50,000 pages			
	. ACCESSORIES				
Paper Feeder		Paper Feeder PF-44 (500 sheets)			

Paper Feeder PF-44 (500 sheets) 8 Monthly Duty Cycle serves as a means of comparison for product robustness in relation to other Canon multi-function laser devices. It does not refer to the actual maximum image output per month

CANON BUSINESS PARTNERS

Canon

Delighting You Always

South & Southeast Asia **Regional Headquarters**

1 Fusionopolis Place, #15-10, Galaxis, Singapore 138522 Tel: 65-6799 8888 Fax: 65-6799 8882

CANON OFFICES

HONG KONG
Canon Hongkong Co. Ltd.
Tel: 852-3191 2388
Fax: 852-2369 3800
www.canon.com.hk

INDIA Canon India Pvt Ltd. Tel: 91-124 416 0000 Fax: 91-124 416 0011

MALAYSIA
Canon Marketing (Malaysia)
Sdn. Bhd.
Tel: 60-3 7844 6000
Fax: 60-3 7845 0505
www.canon.com.my

PHILIPPINES
Canon Marketing (Philippines), Inc.
Tel: 632-884 9090
Fax: 632-556 1456
www.canon.com.ph

SINGAPORE Canon Singapore Pte. Ltd.Tel: 65-6799 8888
Fax: 65-6799 8882

www.canon.com.sa

THAILAND Canon Marketing (Thailand) Co. Ltd. Tel: 66-2 344 9999 Fax: 66-2 344 9960 www.canon.co.th

VIETNAM Canon Marketing Vietnam Co. Ltd. Tel: 84-8 3820 0466 Fax: 84-8 3820 0477

BANGLADESH J.A.N Associates Ltd. Tel: 880-2-966-0601 Fax: 880-2-861-0410 www.jan-bd.com

BRUNEI

CAMBODIA
i-Qlick Marketing Co., Ltd.
Tel: 855-23-996638
Fax: 855-23-996639
www.i-qlick.com

Royal Cambodia Co. Ltd. Tel: 855-23-428955 Fax: 855-23-722961 www.royalcambodia.com.kh

INDONESIA P.T. Samafitro Tel: 62-21 345 5521 Fax: 62-21 384 4271 www.samafitro.co.id

MALDIVES SIMDI Company (Pvt) Ltd. Tel: 960-3334421 Fax: 960-3334424

MYANMAR Myanmar Golden Rock Infernational Co., Ltd. Tel: 95-1 654810 to 19 (10 Lines) Fox: 95-1 654820 Email: sales@mgr.com.mm

NEPAL International Electronics Concern (P) Ltd. Tel: 977-1 4421991 Fxx: 977-1 4421909 www.iec.com.np

PAKISTAN
Shirazi Trading Company (Pvt.) Limited
Tel: 92-21-3241 (7659), (7737) or (7746)
Fax: 92-21-(3241 7747), (3242 0417) or
(3242 0418)
www.shirazitrading.com.pk

SRI LANKA
Metropolitan Office (Pvt) Ltd.
Tel: 94-11 470 0200
Fax: 94-11 470 0267

Dealer's Stamp

0201W548 © 2016 Canon Singapore Pte. Ltd. All rights reserved.

This document is for information purpose only and the contents are subject to change without notice. Product options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations with respect to this document. Canon, imageCLASS, Business Can Be Simple and Canon PRINT Business App are trademarks of Canon inc. and/or its affiliates.

³ The latest drivers for Mac OS and Linux can be downloaded from "www.canon-asia.com" when available.
⁴ Only the print function is supported for Linux.

Measured in accordance with ISO 7779, declared noise emission in accordance with ISO 9296.
 *Inaudible" means that each sound pressure level at bystander's position is less than the ISO 7779 absolute criterion value for background noise level.

Toner cartridge yield is in accordance with ISO/IEC 19752.